

HL4114 data logger

Pro HL4000RH/T Series

Part of the **Hanwell Pro** HL4000RHT Series, the HL4114 combines high accuracy temperature and humidity measurement using an EE07 probe. The instrument includes LCD display.

Features

- ✓ Combined temperature & humidity measurement
- ✓ LCD display with data readings & battery life
- ✓ Superior performance hardware & high accuracy sensors
- ✓ Easily accessible battery & USB socket
- ✓ Logger memory capacity of 50,000 readings per channel
- ✓ Up to 3 year battery life
- ✓ Complies with RoHS, EU & WEEE directives
- ✓ Carries CE Marking

Typical Applications

- Dry storage
- Ambient room conditions

Free HanLog software



Compatible with Hanwell EMS

Instrumentation specification	
Dimension (Excl. ancillaries)	110 x 80 x 35mm
Weight	200 grams
Power supply	1 x 3.6V AA Lithium battery
Case material	ABS & PC
Memory capacity	50,000 readings per channel (unit can be set to wrap or stop when full)
Clock accuracy (logging)	20 ppm at 25°C
IP Rating	IP30
Instrument operating range	-20°C to +65°C in a non-condensing RH environment
Storage temperature	-40°C to +60°C
Resolution	0.1°C (temp), 0.1%RH (humidity)

Product code: HL4114

Data Logger Functions	
Memory	4MB Flash
Logging Intervals	Programmable from 10 seconds to 24 hours
Record Capacity	50,000 readings per channel
Battery life	Up to 3 years (depending on format of data retrieval)
PC Interface	USB Communications
Software required	W200 – HanLog 4.5+ Software Package W300 – HanLog 4.5+ Validated Software Package for Industrial, Food, Pharma & Hospital

Accessories	
Y119	Wall mounting bracket
88706	AA Lithium battery
Y421-3	EE Probe extension lead 3 meters
Y421-5	EE Probe extension lead 5 meters



Temperature



Humidity



Data logger



Ultimate peace of mind



RoHS

Version 1 - EC180002

Disclaimer: The information contained herein is believed to be reliable. Hanwell Ltd is not responsible for any Customers should obtain and verify the latest relevant information before placing orders for Hanwell products.

hanwell.com

Sensor options (supplied separately)

J140 EE07-02 RH/T probe

Temperature Probe	PT1000 (Tolerance class A)
Temperature operating range	-40°C to +80°C (restricted by instrument operating range)
Cable operating range	-40°C to +80°C
Temperature accuracy	+/- 0.1°C at 20°C (see temp accuracy chart)
Long term drift	+/- 0.05 ° C
Humidity Probe	Capacitive Polymer
Recommended range	0-100% RH non condensing
Accuracy	+/- 2% (0-90%) +/- 3% (90-100%)
Temperature dependance	<(0.025+0.0003xRH)[%RH/°C]

Temperature accuracy chart for EE07 probe

