

MEETINSTRUMENTATIE

Turfschipper 114 | 2292 JB Wateringen | Tel. +31 (0)174 272330 | www.catec.nl | info@catec.nl

RL4810 transmitter

Pro RL4800 Series

Part of the Hanwell RL4800 series of radio transmitters, the RL4810 is a single channel transmitter with a 0-5VDC input for use internally or externally. Each unit includes a steel bracket for mounting purposes.

Features

- \checkmark Single 0-5VDC input for air flow, pump, level and door alerts
- \checkmark 100,000 data readings & up to 18 months battery life
- √ Superior performance hardware & high accuracy sensors
- Easily accessible battery
- √ Low power radio for long distance transmission (3km over open ground)
- √ Complies with RoHS, EU & WEEE directives
- √ Carries CE Marking

Typical Applications

- · Level measurement
- Door open/close alerts
- Machine on/off alerts

Always ask for a long-range signal strength test.



We can prove ours to be unrivalled.

recnnical specification	
Dimensions	110 x 80 x 35mm
Weight	200 grams
Power supply	3.6V AA Lithium battery
Case material	ABS & PC
Cable length	3m with bare ends (as shown in image)
Memory capacity	100,000 readings (unit will wrap when full)
Clock accuracy (logging)	20 ppm @ 25°C
Instrument operating range	-20°C to +65°C (non-condensing RH environment)
Storage Temperature	-40°C to +60°C
IP Rating	IP30

Accessories	
88706	AA 3.6V Lithium battery













B 1	DI 4040 404 075	
Product code:	RL4810-434.075	(other frequencies are available)

Radio transmitter functions		
Frequency options	A range of frequencies are available between 433-458MHz. Country specific regulations apply.	
Radio power	10mW	
Radio range	3km over open ground	
Battery life	Up to 18 months (dependent on conditions of use and instrument settings)	
Software required	W900 – Standard EMS Software Package W906 – Validated EMS Software Package *See EMS datasheet for further options	
Hardware required	SR2 – Smart Receiver REP – Repeater	
Input		
Input	Single channel 0 to 5 V	
Measuring frequency	Every transmit/log interval	
Transmit interval	User programmable 30s-300s	
Resolution	0.00125V	
Accuracy	+/-1%	





